

Amendments To The Claims:

This listing of claims will replace all prior versions or listing of claims for this application:

Listing of Claims:

A7
SUBB7

1. (Currently amended) A disk reproducing apparatus comprising:

- a main body;
- a frame which is pushed out from[,] or drawn in said main body[,];
- a disk tray which is rotatably attached to said frame[,] and has a plurality of turn tables for mounting a plurality of disks; and
- an optical pick-up unit for reproducing or recording data ~~recorded from or~~ in said disk; ~~and~~
- ~~a turn table for holding and rotating said disk~~
- ~~wherein said optical pick-up unit operated along with a turn table for holding and rotating said disk,~~ is located between a rotation center of said disk tray and ~~said a~~ front panel of said main body ~~in said state in that~~ when said frame is drawn in said ~~reproducing~~ apparatus main body.

2. (Currently amended) A disk reproducing apparatus comprising:

- a main body;
- a frame which is pushed out from[,] or drawn in said main body[,];
- a disk tray[,] which is rotatably attached to said frame[,] and has a plurality of turn tables for mounting a plurality of disks; and
- an optical pick-up unit for reproducing or recording data ~~recorded~~ in said disk;

A7
Came!

~~wherein said optical pick-up unit operated along with a turn table for holding and rotating said disk, when said frame is drawn in said main body, said optical pick-up unit is provided on said main body at an angle of 36 degrees – 108 degrees, which is located between a line drawn from a rotation center of said disk tray and a front panel of said main body and said rotation center of said disk tray, to a rotation center of said turn table, where said one turn table is located in a reproducing position of said optical pick-up unit, and a line drawn horizontally from the rotation center of said disk tray to a front panel of the main body at a rotation angle range of 36 – 108 deg., in said state in that said frame is drawn in said main body.~~

3. (Currently amended) A disk reproducing apparatus comprising:

a main body;

a frame which is pushed out from[,] or drawn in said main body[,];

a disk tray, which is rotatably attached to said frame, for mounting a plurality of disks; and

an optical pick-up unit for reproducing recording data recorded in said disk;

wherein said optical pick-up unit operating along with a turn table for holding and rotating each disk, is located so that a line between a rotation center of said disk tray and a rotation center of said turntable intersects a line virtually drawn perpendicularly ~~between a front panel of said main body and from~~ the rotation center of said disk tray plate to a front panel of said main body, at a rotation angle range of 36 degrees – 90 degrees, ~~in the state in that when~~ said frame is drawn in said main body.

Claim 4 (Canceled).